

120 TON



FIVE WORKSTATIONS:

- **Standard (4)** - Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- **Open (1)** - Customize your ironworker with 4 optional Attachments - Brake, Rod Shear, Multi-Shear & Pipe Notcher
- 10 interchangeable Attachments available to tailor the Ironworker to your project. See pages 20 and 21 for options



- Available with PowerLink™ System to increase your capabilities with our ever expanding line of Hydraulic Tools
- ANSI B11.5- 1988(O2) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stroke control

SPECIFICATIONS	
Punch Rating (tons)	120
Punch Max. Capacity (in.)	1-1/2 diam. in 1 in Mild Steel
Angle Shear Max. Capacity (in.)	6 x 6 x 1/2
Flat Bar Shear Max. Capacity (in.)	1/2 x 24 1 x 12
Coper Notcher Max. Capacity (in.)	3 x 6 x 1/2
Standard Motor	10 HP 3 Ph 230V
Dimensions (in.)	79-3/8 x 60 x 60
Weight (lbs.)	5500

STOCK NUMBER	PRODUCT DESCRIPTION
IW120-1P230	120 Ton Ironworker 230V, 1Ph
IW120-3P208	120 Ton Ironworker 208V, 3Ph
IW120-3P230	120 Ton Ironworker 230V, 3Ph
IW120-3P460	120 Ton Ironworker 460V, 3Ph
IW120-3P575	120 Ton Ironworker 575V, 3Ph



STOCK NUMBER	PRODUCT DESCRIPTION
IW120-1P230-AC900	120 Ton Ironworker 230V, 1Ph with PowerLink
IW120-3P208-AC900	120 Ton Ironworker 208V, 3Ph with PowerLink
IW120-3P230-AC900	120 Ton Ironworker 230V, 3Ph with PowerLink
IW120-3P460-AC900	120 Ton Ironworker 460V, 3Ph with PowerLink
IW120-3P575-AC900	120 Ton Ironworker 575V, 3Ph with PowerLink