



IRONWORKERS

60 TON

4
WORK STATIONS



FOUR WORKSTATIONS:

- **Standard (4)** - Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- 9 additional Attachments available to convert the Punch Workstation to your specific needs. See pages 20 and 21 for options



- Available with PowerLink™ System to increase your capabilities with our ever expanding line of Hydraulic Tools
- ANSI B11.5-1988(O2) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stroke control

SPECIFICATIONS

Punch Rating (tons)	60
Punch Max. Capacity (in.)	1 diam. in 3/4 in Mild Steel
Angle Shear Max. Capacity (in.)	3 x 3 x 1/2 4 x 4 x 3/8
Flat Bar Shear Max. Capacity (in.)	3/8 x 14 1/2 x 12 3/4 x 4
Opt. Coper Notcher Max. Capacity (in.)	2 1/2 x 4 x 3/8
Standard Motor	5 HP 3 Ph 230V
Dimensions (in.)	56-1/8 x 46-1/8 x 36-1/8
Weight (lbs.)	2550

STOCK NUMBER

PRODUCT DESCRIPTION

IW60-1P230	60 Ton Ironworker 230V, 1Ph
IW60-3P208	60 Ton Ironworker 208V, 3Ph
IW60-3P230	60 Ton Ironworker 230V, 3Ph
IW60-3P460	60 Ton Ironworker 460V, 3Ph
IW60-3P575	60 Ton Ironworker 575V, 3Ph



STOCK NUMBER

PRODUCT DESCRIPTION

IW60-1P230-AC500	60 Ton Ironworker 230V, 1Ph with PowerLink
IW60-3P208-AC500	60 Ton Ironworker 208V, 3Ph with PowerLink
IW60-3P230-AC500	60 Ton Ironworker 230V, 3Ph with PowerLink
IW60-3P460-AC500	60 Ton Ironworker 460V, 3Ph with PowerLink
IW60-3P575-AC500	60 Ton Ironworker 575V, 3Ph with PowerLink