



# 65 TON

## Our Most Versatile Machine

- Five Available Workstations
- E-Stop/Lockout-Tagout
- Universal Open Tooling Station
- 24" Flat Bar Shear
- Dedicated Coper Notcher
- Electric Stroke Control
- ANSI B11.5-1988R(02) Compliant
- ETL/UL Approved Controls

The five workstations of the Edwards 65 Ton JAWS Ironworker provide the power to handle any size job and the flexibility to tailor it to your specific needs. Standard features include a Punch Assembly with Pedestal Die Table, 24" wide Flat Bar Shear, Angle Shear, Coper Notcher and a universal open tooling station designed to accept a variety of optional Tooling Accessories.



### PUNCH

Rating:	65 Tons
Max. Capacity:	1-1/16" Dia. in 3/4" A36
Stroke:	1-13/16"
Throat Depth:	9-3/4"
Open Height:	8-3/4"
Shut Height:	6-15/16"
Work Height:	36-9/16"

### ANGLE SHEAR

Max. Capacity:	5" x 5" x 3/8"
Work Height:	43-1/2"

### FLAT BAR SHEAR

Max. Capacity:	3/8" x 24"
	1/2" x 14"
	1" x 4"
Max. Round:	1"
Max. Square:	1"
Work Height:	34-1/2"

### COPER NOTCHER

Max. Capacity:	2-1/2" x 5" x 3/8"
Work Height:	39-1/2"

### OPEN CAVITY

Height:	8-3/4"
Width:	12"
Work Height:	43"

### GENERAL SPECIFICATIONS

Standard Motor:	7.5 HP 3~ 208 V or 230 V	1765 RPM 22 A
Optional Motors:	7.5 HP 3~ 460 V	1765 RPM 11 A
	7.5 HP 3~ 575 V	1770 RPM 8 A
	5 HP 1~ 208 V or 230 V	1725 RPM 23 A
	*7.5 HP 1~ 230 V	1765 RPM 36 A

*\*Required for 1~ Hydraulic Accessory Pack*

Hydraulic Pump:	10-1/2 GPM - 2 Stage
Valve Pressure:	3500 PSI
Reservoir:	17 Gallons
Cylinder:	3-1/2" Ram

### DIMENSIONS

Height:	57"
Width:	62-1/8"
Depth:	45"
Shipping Weight:	4750 lb