

65 TON

5
WORK STATIONS



FIVE WORKSTATIONS:

- **Standard (4)** - Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- **Open (1)** - Customize your ironworker with 4 optional Attachments - Brake, Rod Shear, Multi-Shear & Pipe Notcher
- 10 interchangeable Attachments available to tailor the Ironworker to your project. See pages 20 and 21 for options



- Available with PowerLink™ System to increase your capabilities with our ever expanding line of Hydraulic Tools
- ANSI B11.5- 1988(O2) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stroke control

SPECIFICATIONS

Punch Rating (tons)	65
Punch Max. Capacity (in.)	1-1/16 diam. in 3/4 in Mild Steel
Angle Shear Max. Capacity (in.)	5 x 5 x 3/8
Flat Bar Shear Max. Capacity (in.)	3/8 x 24 1/2 x 14 1 x 4
Opt. Coper Notcher Max. Capacity (in.)	2-1/2 x 5 x 3/8
Standard Motor	7.5 HP 3 Ph 230V
Dimensions (in.)	57 x 62-1/8 x 45
Weight (lbs.)	4750

STOCK NUMBER

PRODUCT DESCRIPTION

IW65-1P230	65 Ton Ironworker 230V, 1Ph
IW65-3P208	65 Ton Ironworker 208V, 3Ph
IW65-3P230	65 Ton Ironworker 230V, 3Ph
IW65-3P460	65 Ton Ironworker 460V, 3Ph
IW65-3P575	65 Ton Ironworker 575V, 3Ph



STOCK NUMBER

PRODUCT DESCRIPTION

IW65-1P230-AC700	65 Ton Ironworker 230V, 1Ph with PowerLink
IW65-3P208-AC600	65 Ton Ironworker 208V, 3Ph with PowerLink
IW65-3P230-AC600	65 Ton Ironworker 230V, 3Ph with PowerLink
IW65-3P460-AC600	65 Ton Ironworker 460V, 3Ph with PowerLink
IW65-3P575-AC600	65 Ton Ironworker 575V, 3Ph with PowerLink