

ELITE 110/65



FIVE WORKSTATIONS:

- **Standard (4)** - Punch, Flat Bar Shear, Angle Shear & Coper Notcher
- **Open Cavity (1)** - Customize your ironworker with 4 optional Attachments - Brake, Rod Shear, Multi-Shear & Pipe Notcher
- 9 interchangeable Attachments available to tailor the Ironworker to your project. See pages 20 and 21 for options



- Standard PowerLink™ System increases your capabilities with our ever expanding line of Hydraulic Tools
- Two independent power plants for true dual operation
- Hydraulic Hold-Down
- Quick Change Punch Assembly
- Swing-Away Stripper Assembly
- Roller Encoder Measuring System
- Premium Gauging Tables
- LED Lighting
- Central Lubrication System
- ANSI B11.5- 1988(02) Compliant Guarding
- ETL/UL Approved Controls
- Integrated E-Stop, Lock-out/Tag-out
- Optimized workstation heights for improved efficiency
- Electric foot pedals with integrated jog control
- Adjustable electric stoke control

SPECIFICATIONS

Punch Rating (tons)	110
Punch Max. Capacity (in.)	1-3/8 diam. in 1 in Mild Steel
Angle Shear Max. Capacity (in.)	5 x 5 x 3/8
Flat Bar Shear Max. Capacity (in.)	3/8 x 24
	1/2 x 14 1 x 4
Coper Notcher Max. Capacity (in.)	5 x 5 x 3/8
Standard Motor	7.5HP 3 Ph 230V
Dimensions (in.)	65-1/8 x 91-9/16 x 44-7/8
Weight (lbs.)	8580



STOCK NUMBER	PRODUCT DESCRIPTION
ELT11065-1P230	110/65 Ton Elite Dual Operator Ironworker 230V, 1Ph
ELT11065-3P208	110/65 Ton Elite Dual Operator Ironworker 208V, 3Ph
ELT11065-3P230	110/65 Ton Elite Dual Operator Ironworker 230V, 3Ph
ELT11065-3P460	110/65 Ton Elite Dual Operator Ironworker 460V, 3Ph
ELT11065-3P575	110/65 Ton Elite Dual Operator Ironworker 575V, 3Ph